

Storm Management Handbook



12

Professional Development Hours (PDH) or Continuing Education Hours (CE) Online PDH or CE course

Contact information

www.DiscountPDH.com

fdapdh@gmail.com

Telephone: 713-787-6810

Corporate Mailing address: 2500 Tanglewilde, Suite 220 Houston, Texas 77063

For all your questions and instructor support please contact us via email or phone. All emails and phone calls are addressed within 24 hours. Operating hours: 9 am – 4 PM central time Tel: 713-787-6810

Email: fdapdh@gmail.com

Fax: 713-787-6825

FDA, Inc.

FDA, Inc.

Execu	tive Su	mmary	I				
1.0	GENERAL BACKGROUND						
	1.1	A Green Infrastructure Approach to Stormwater Management	3				
2.0	A REGIONAL GREEN INFRASTRUCTURE APPROACH						
	2.1 Preserving Open Space						
	2.2	Encouraging Growth in Already Developed Areas	7				
3.0	A NEIGHBORHOOD-SCALE GREEN INFRASTRUCTURE APPROACH						
	3.1	Compact Mixed-Use Development	9				
	3.2	Revising Street Design Standards					
	3.3	Revising Parking Requirements	12				
4.0	GREEN INFRASTRUCTURE STRATEGIES FOR SITE DESIGN						
	4.0	Introduction					
	4.1	Green Roofs					
	4.2	Pervious Paving					
	4.3	Rainwater Harvesting	20				
	4.4	Stormwater Swales					
	4.5	Stormwater Planters					
	4.6	Infiltration Gardens					
	4./	Stormwater Curb Extensions					
	4.8	Residential Downspout Disconnection					
5.0	THE DESIGN STRATEGIES IN NORTHERN KENTUCKY						
	5.I	Residential Streets	41				
		Stormwater Curb Extensions	42				
		Mid-Block Stormwater Curb Extension Applications	44				
		Options for New Development					
		Pervious Paving in the Parking Zone					
	ΓA	Residential Alley Swales	50				
	5.2	Commercial Main Streets					
		Main Street with Stormwater Planters	ـــــــــــــــــــــــــــــــــــــ				
		"Green Gutter" Narrow Planter					
		Curb Extensions and Penvious Paving in Parallel Parking Zone					
		Angled Parking Solutions	60				
		Converting "Grav Space" into "Green Space"	62				
		An Urban Alley Retrofit					
	5.3	Arterial Streets and Boulevards					
		Four-Lane Arterial: Retrofit or New Construction					
		Oversize Sidewalk Converted Into a Stormwater Swale					
		Option for an Arterial Street With Multiple Swales	67				

	5.4	Parkin	g Lots	68
		Parkin	g Lot With Side Swale	69
		Side S	wale in Parking Lot With Angled Parking	70
		Cente	r Median Stormwater Swale in a Parking Lot	72
		Parkin	g Lot Infiltration Garden	74
		Parkin	g Lot With Pervious Paving and Stormwater Planters	75
	5.5	Buildir	1gs	76
		Found	lation Planting Converted into a Rain Garden	77
		Small	Roof To Green Roof	78
		Reside	ential Rain Garden Retrofit	79
6.0	PUTT	ING IT	ALL TOGETHER: APPLYING GREEN INFRASTRUCTURE AT THE	
	REGIO		AND NEIGHBORHOOD SCALE IN NORTHERN KENTUCKY	80
	6.1	The F	Riverfront	82
	6.2	City ⊢	leights	83
	6.3	Laton	a Terrace	
	6.4	The R	etail Center	90
		JSION		91
APPE		S		93
	Apper	ndix A:	FPA Smart Growth Implementation Assistance	
	Apper	ndix B:	Stormwater Strategy Matrix	
	Adder	ndix C:	Street Profile	
Appendix D: Appendix E: Appendix F: Appendix G:			Pedestrian Circulation	
			Dealing With Steep Topography	
			Designing With Trees	102
			Getting the Water In - Sheet Flow or Curb Cuts?	103
	Apper	ndix H:	Types of Curb Cuts	104
Apper Apper		ndix I:	Conveying Water With Trench Drains and Speed Bumps	107
		ndix J:	Dealing with Sediment	108
	Apper	ndix K:	Overflow Options	109
	Apper	ndix L:	Soil Preparation	
	Apper	ndix M:	Protecting The Building Foundation	
	Apper	ndix N:	Long-Term Maintenance Considerations	112
	Apper	ndix O:	Additional Resources	113

EXECUTIVE SUMMARY

This handbook is a guide to help Northern Kentucky communities manage, and reduce, their stormwater runoff while still allowing the region to grow and prosper with more homes, businesses and jobs. Where and how development occurs in Northern Kentucky can dramatically affect the region's watersheds, wastewater treatment systems, and water supplies. Effectively engaging at the regional, neighborhood, and site scales can help Sanitation District No. I (SDI) address regulatory requirements and help Northern Kentucky communities to better balance development decisions with environmental protection.

This handbook includes land use policies and strategies that could be applied regionally across Northern Kentucky and in other areas of the United States to reduce stormwater runoff volumes without hindering growth. Communities in other areas of the US have found these strategies to be effective at reducing stormwater volumes while allowing for economic growth and creating attractive, livable neighborhoods. Strategies include preserving open space that both improves water quality and provides recreational opportunities and wildlife habitat, and using land efficiently by directing growth to already developed areas.

Equally important as where development is located is how it is built. The handbook, therefore, looks at development strategies and policies such as compact development, mixed-use zoning, and revised street and parking standards. These practices no only manage stormwater, but also create streets that invite visitors and residents to walk, and provide a setting for shops, cafes and restaurants that cater to pedestrians.

The majority of the handbook illustrates innovative sitelevel design strategies that reduce runoff from development and how they could be successfully applied in Northern Kentucky. The strategies, policies, and designs illustrate the handbook's goal– to provide communities in Northern Kentucky environmentally responsible planning and design alternatives that can reduce water pollution, decrease runoff volume, protect aquatic habitat, and have the additional community benefit of creating more interesting places to live, work and play.





Figure 1-1: A creek in Northern Kentucky.

SD1 is the agency responsible for collecting and treating wastewater and managing stormwater in the counties of Boone, Campbell, and Kenton, located along the southern bank of the Ohio River, across from the city of Cincinnati. SDI's service area has in recent years experienced rapid population growth, which has strained the capacity of the region's sewer systems. At the same time, development has paved over more land for buildings, roads, and parking lots. This has increased the amount of stormwater runoff, since paved, or "impervious," land cannot absorb stormwater, which instead runs off the surface. Population growth and land development in Northern Kentucky have contributed to numerous sewer overflows from both the combined and the sanitary sewer systems. In April 2007, SDI, as the regional wastewater and stormwater utility, entered into a consent decree with the U.S. Environmental Protection Agency (EPA), the Kentucky Energy and Environment Cabinet, and the U.S. Department of Justice to address these sewer overflows.

The consent decree calls for a comprehensive watershed approach for assessing and addressing all sources of water pollution in the region and the cumulative impacts of these sources on receiving waters. The watershedbased approach is expected to attain faster improvements in water quality. This approach can also create places that are environmentally and economically sustainable, interesting, and attractive places to live, work and play.

To assist SDI, EPA provided a team of

consultants to participate in a design workshop that discussed how Northern Kentucky communities could grow and prosper while addressing stormwater issues and the requirements of the consent decree (see Appendix A for a description of EPA technical assistance program and the workshop objectives). Residents and other stakeholders who participated in the workshop repeatedly voiced a desire for attractive and economically vital communities and the safe, walkable streets. This handbook presents green infrastructure strategies that SD1, Northern Kentucky communities, and other communities in the US, could adopt to manage stormwater at the regional, neighborhood, and site scales while also while creating safe, attractive and walkable communities. This handbook is not a technical manual for engineering and construction. For those purposes, refer to the Sanitation District No. I Best Management Practices Manual available from SD1.

One approach that will enable SD I to address the requirements of the consent decree and create additional community benefits are green infrastructure strategies. A green infrastructure approach to stormwater management means using the landscape's inherent ability to slow, filter, and absorb rainfall as close as possible to where it hits the ground. This approach reduces the frequency and intensity of overflows from combined sewers. It also reduces the risk of flooding, polluted runoff, and erosion to stream channels caused by a high volume of runoff (Figure 1-3).

A comprehensive green infrastructure approach applies to development at the regional, neighborhood and site scale and includes the following concepts:

Preserve: Protect and enhance natural features, such as undisturbed forests, meadows, wetlands, and other natural areas.

Recycle: Recycle land by directing development to already degraded land, e.g., parking lots, vacant buildings, or abandoned malls.

Reduce: Reduce land consumption and the development footprint by using land efficiently.

Reuse: Capture and reuse stormwater by directing it back into the ground through infiltration, reusing it for other purposes such as irrigation, or allowing it to evaporate.



Figure 1-2: The conventional approach to stormwater management is treating rainfall runoff as a waste rather than a resource.



Figure 1-3: Urban runoff affects natural systems in a wide variety of ways such as stream bank erosion.



Figure 1-4: The Sustainable Stormwater Design Model: A balance of economy, ecology, and community.

Rolling hills, woods, pastures, and river and stream channels give Northern Kentucky a unique sense of identity and provide valuable water quality benefits by absorbing much of the region's rainfall. Conventional low-density development evident in much of region not only diminishes the scenic beauty but also contributes to degradation of the region's streams and rivers. Growth provides employment, housing, and recreational and cultural opportunities, but it can be designed and planned to use land efficiently, reinforce a community's "sense of place," and improve the region's water quality. Two complementary strategies at the regional scale could help Northern Kentucky achieve its water quality goals while allowing the region to grow and prosper:

- Preserving open space; and
- Encouraging growth in already developed areas.

Figure 2-2, a drawing of the Covington area produced during the design workshop, illustrates how thinking at a larger, city-wide scale can have water quality benefits, promote continued growth, and create multiple recreational and community benefits. The organizing "framework" for the drawing is an open space network connecting downtown Covington, the city's major parks and open spaces, with the Ohio and Licking Rivers. Preserving open spaces does not restrict growth in the city since there are significant redevelopment opportunities on sites that are either vacant or underused. Redevelopment of these sites could create pleasant, walkable neighborhoods and catalyze revitalization in surrounding neighborhoods—without contributing increased runoff to the combined sewer system. In fact, new development that adopts the land use and design recommendations outlined in this handbook could actually reduce runoff volume while also reducing growth pressures on the region's natural lands. Allowing growth and managing stormwater is a win-win situation for the region.

Similar strategies could be applied to less urban communities across Northern Kentucky's three counties. The steps are similar: preserve high-priority open spaces such as forests, meadows, stream corridors, and steep hillsides that not only absorb rainfall, but also provide valuable opportunities for recreation and wildlife habitat. Next, identify possible areas of redevelopment, such as vacant industrial lands or an underused regional retail center; and then use the land efficiently by considering a mix of land uses and housing that includes townhomes, apartments and condominiums.



Figure 2-1: Managing growth effectively and preserving open space can protect water quality in creeks, streams, and rivers in Northern Kentucky.



Figure 2-2: Redeveloping areas in Northern Kentucky that are currently under-performing can help direct growth away from open space.

Preserving open space in the Northern Kentucky region is critical to maintaining water quality and reducing runoff, but it does not mean that growth opportunities need be restricted. The investment in open space "pays back" by reducing runoff and flooding risks, protecting scenic character, providing wildlife habitat, and creating recreational opportunities for the area's residents and visitors. The following are some tools that Northern Kentucky communities could use to preserve open space:



Lenexa, Kansas, is a growing suburb in metropolitan Kansas City that faces increasing pressure from the impacts of new development and associated increases in stormwater runoff. In an effort to protect local water quality, as well as prevent flooding and improve the quality of life for residents, Lenexa's comprehensive plan, Vision 2020. initiated Rain to Recreation, an innovative and integrated watershed protection program. The program outlines a number of policies and programs to protect land from future development and introduce new green infrastructure practices that limit imperviousness and manage runoff on-site, including protection of priority natural resource areas in the watershed, to creation of riparian greenways through the application of a stream setback ordinance, to requiring low-impact development practices on site, Lenexa is investing in green infrastructure at all three scales, including the regional watershed, neighborhood, and site levels.

•Transfers of development rights (TDRs) allow a community to direct development to areas targeted for growth while preserving undeveloped land elsewhere. Purchases of development rights (PDRs) operate similarly to TDRs except that the developer is required to purchase those development rights.

•Up-zoning and down-zoning are practices that can be used individually or in tandem with TDR/PDR programs. These tools restrict development in areas that are more appropriately left undeveloped while encouraging more efficient use of land targeted for growth.

•Conservation easements, or conservation restrictions, are legal agreements between a landowner and a land trust or government agency that allow the landowner to continue to own and use the land and to sell it or pass it on to heirs. The landowner gives up some of the rights associated with the land, such as the ability to develop it.

•Buffer ordinances would require vegetated zones between waterways and proposed developments in order to protect water quality.

•Steep-slope ordinances would place development restrictions on areas that, due to their topography, are particularly susceptible to erosion and sediment loss. Just as communities in Northern Kentucky can use the land to absorb rainfall, they can identify locations in the region that can absorb future development without consuming valuable open space. Using land more efficiently reduces and better manages stormwater runoff by reducing total impervious area. The most effective strategy for efficient land use is redeveloping already degraded sites such as abandoned shopping centers or underused parking lots rather than paving greenfield sites. The drawing of Covington (Figure 2-2) identified some possible redevelopment opportunities on sites with underused parking lots, and Figure 3-4 in the following section illustrate a development plan for one of the sites. By redeveloping an underused site that is already paved, the net increase in runoff from development would likely be zero–or actually decrease, depending on the on-site green infrastructure practices used (presented in Chapter 4). Northern Kentucky communities have the options of directing and concentrating new development in areas specifically targeted for growth. By doing so communities can reduce development pressure on undeveloped parcels, protect sensitive natural lands, provide access to open space for recreational purposes, and create more vibrant neighborhoods. In addition to TDRs/PDRs and up-zoning and down-zoning mentioned previously, additional tools can direct growth to already developed areas:

• Priority funding areas use financial incentives to direct growth to already developed areas or to areas targeted for development.

- Local government incentives such as density bonuses and accelerated permitting process for infill and redevelopment projects.
- •Reduced impact fees for infill development based on less demand for new infrastructure.
- •Differentiating sewer and water connection fees would allow municipalities and utility authorities to offer discounts for development in desired areas.
- •Capital or financing from local governments for infrastructure improvements (water, sewer, road, sidewalk, etc. upgrades) in identified growth areas.
- •Tax Incremental Financing districts to encourage redevelopment.
- •Stormwater management requirement provision that reduces on site management requirements for projects that decrease total imperviousness on previously developed sites
- •Large-lot/agricultural zoning (e.g., 1 unit/160 acres) outside of growth boundary or at the edge of a city to restrict development and to preserve rural character.



The redevelopment of the former Mizner Park shopping mall in Boca Raton, Florida, illustrates the opportunities of redevelopment. Originally a large retail structure surrounded by surface parking lots, the 29-acre site now designed as a village within the city. The project has a residential density five times higher than the rest of the city and a mix of large and small retailers, restaurants and entertainment venues. The final build-out of Mizner Park decreased overall impervious surface by 15 percent by replacing asphalt with a landscaped plaza, flower and tree planters and an amphitheater.



Figure 3-1: The shaded areas in this diagram represent the impervious area associated with streets.



Figure 3-2: The shaded areas in this diagram represent the impervious area associated with streets and buildings in the same neighborhood represented in Figure 3-1.



Figure 3-3: The shaded areas in this diagram represent the impervious area associated with streets, buildings, and parking lots, again in the same neighborhood.

Regional decisions of where to develop will be accompanied by equally important decisions at the neighborhood scale of how to build new development. Neighborhood scale green infrastructure approaches reduces imperviousness by compacting development and integrating natural features into streets and parking lots. This chapter looks at three neighborhoodscale strategies that could help Northern Kentucky communities reduce stormwater runoff and associated pollutants while creating more interesting and attractive neighborhoods:

- Compact mixed-use development;
- Revised street design standards; and
- Revised parking requirements.

Strategies in this chapter can be thought of as creating the "space" in which the site-level designs presented in Chapter 4 can be incorporated.

Figure 3-4 is a conceptual plan that illustrates an infill neighborhood development in Covington that uses land efficiently. The development replaces a retail center with a new neighborhood that has a mix of uses closer together, making it easier for people to walk, bike, or take transit to meet their daily needs. Not only do the narrower streets, smaller parking areas, and "pocket parks" significantly reduce runoff in comparison to the previous use, they also improve community character and could spark revitalization in adjacent neighborhoods.

Figures 3-1 through 3-3 are diagrams of the neighborhood that surround the concept plan area in Figure 3-4 (the area of the concept plan is in the lower left corner of the diagrams). At this scale, the amount of impervious surface associated with the conventional design of streets, parking lots, and buildings becomes apparent. These surfaces are the most significant contributors to the volume of runoff that causes combined sewer overflows (CSOs) into the rivers and streams of Northern Kentucky. In areas of the region with separated sewer systems where the storm sewers discharges directly into the waterways, the volume of stormwater runoff erodes the river and stream banks, and the pollutants picked up by the runoff degrade water quality.



Figure 3-4: New and existing neighborhoods, such as this conceptual example in Covington, Kentucky, could increase density, preserve open space, and introduce more site-level stormwater strategies.

> IMPLEMENTING GREEN INFRASTRUCTURE IN NORTHERN KENTUCKY COMMUNITIES 9

Compact, mixed-use development is not a new planning concept in Northern Kentucky. Many of the region's older downtowns and neighborhood centers have homes, shops, offices, and schools built closer together and connected by a fine grid of streets that allow people to walk, bike or take transit in order to meet their daily needs. This approach not only replicates the pedestrian-friendly character of the older parts of the cities, but also benefits water quality by reducing the overall amount of impervious surface dedicated to streets and parking lots. Recreating such neighborhoods today can sometimes be difficult because of inflexible planning and zoning regulations. Several tools can help communities address these barriers:



Figure 3-5: New and existing neighborhoods can be built to increase density, preserve open space, and introduce more site-level stormwater strategies.



Figure 3-6: Traditional neighborhood development space, creates attractive maximizes green communities, and provides more pedestrian and bike connectivity.

•Form-based zoning codes regulate building appearance rather than density and use. By stressing the appearance of the streetscape or the public realm, form-based codes allow greater development intensity while still promoting good design.

•Traditional Neighborhood Development (TND) codes, a subset of mixed-use codes, seek to replicate the look and feel of attractive, old-fashioned neighborhoods with a combination of street grid, short blocks, pedestrian orientation, and architectural interest.

•Planned unit developments (PUDs) are zoning overlays that allow several parcels in a subdivision to be planned as a single unit. This provides flexibility in parking and open space requirements and/or mixing land uses.

•Overlay zoning districts permit increased density or development intensity in areas where this is appropriate, such as downtowns, along commercial corridors, or near transit stations.

• Density bonuses allow a developer to increase the number of housing units or square feet of commercial or office space if specific design criteria are met, such as including a green roof or developing an infill site.

Streets offer unique opportunities for handling and treating their runoff, but conventional street design practices focus primarily on moving the automobile and diverting runoff to the curb and gutter, contributing to increased runoff volume and poor water quality. Figures 3-7 and 3-8 illustrate the before-and-after concept of a street in Covington that could be redesigned to better manage stormwater runoff. Space in the street is reallocated to accommodate a bike lane and landscaping that improves the look of the street as well as manages stormwater. The narrower street still safely accommodates cars. The following are some tools that communities could consider to create more attractive, environmentally responsible streets:

•Reducing street widths provides a host of benefits, including less impervious surface, more attractive streetscapes, slower traffic speeds, and improved safety for pedestrians and cyclists. Communities could review their street-width standards— usually found in their zoning or subdivision regulations—and require the minimum travel-lane and right-of-way widths necessary to meet safety and traffic concerns.

•Adopting "Green Streets" design standards would provide better environmental performance while creating more attractive and safe environments. Green street features include: landscaped medians, planted curb extensions, planter strips along sidewalks, street trees, and pervious paving, all of which are illustrated in the Chapter 4.



Figure 3-7: A typical urban street in downtown Covington, Kentucky.



Figure 3-8: The same street redesigned to accommodate a new bike lane, enhanced landscaping, and stormwater management.



Figure 3-9: Well-landscaped streets, such as this example in Chicago, Illinois, provide a unique and attractive character to neighborhoods.



Figure 3-10: This photo shows a large parking lot in Northern Kentucky that is underused.



Figure 3-11: Shortening these oversized parking spaces by just a few feet could create space for swales.



Figure 3-12: Here, shorter parking stalls yielded space for landscape-based stormwater management.

Parking lots, like streets, make up large areas of impervious surface across Northern Kentucky and contribute to polluted runoff. Communities in the region could consider the following tools to reduce impervious surface for parking and allow the space in a parking lot to be reallocated to accommodate sustainable stormwater management features (which are discussed in Chapter 4):

 Set appropriate parking ratios for development projects that, because of their location, users, or project features, can be expected to have lower-than-average parking demand. Such land uses include compact, mixed-use, and transitoriented developments; those in downtowns, near transit stations and along commercial corridors; and those catering to students, the elderly, and other demographic groups with lower-than-average car ownership rates.

•Allow businesses to count underused nearby on-street parking spaces toward meeting their parking requirements.

•Shared parking reduces the number of spaces that each development has to provide while still meeting the needs of drivers. For example, an office building parking lot might be full during the day but empty at nights and weekends. Sharing a parking lot with a movie theater, where demand is greatest at night and on weekends, would reduce the total parking required.

• Provide transportation alternatives that reduce the need for parking by encouraging people to carpool, use transit, walk, bike, telecommute, or shift their trips to non-peak periods. These are most often implemented by employers.

This section provides developers, designers, policy makers, and the general public with a toolbox of site-level design strategies to consider that can protect water quality and make streets and development more attractive in Northern Kentucky. Site-level strategies build off of the regional and neighborhood-scale strategies presented in Chapters 2 and 3, and are divided into two categories: Rain-Absorbing Footprint Strategies and Rain Garden Strategies. Supporting technical information is provided in the Appendix.

Rain-Absorbing Footprint Strategies design streets, parking lots, and buildings to absorb as much rainwater as possible. They use alternative surface materials to make otherwise impervious surfaces pervious or collect water for reuse. Green roofs and harvesting strategies are particularly appropriate in locations in Northern Kentucky with clay soils. Practices include:

- Green roofs;
- Pervious paving; and
- Rainwater harvesting.

Rain Garden Strategies use plants and soils to filter, absorb, and slow rainwater on the landscape surface. They are vegetated depressions in the landscape with plants adapted to inundation and drought. Types of rain garden practices include:

- Swales;
- Planters;
- Infiltration gardens;
- Curb extensions; and
- Residential downspout disconnections.

One of the simplest strategies to manage stormwater runoff on site is to preserve and protect a site's existing natural resources, such as stands of trees, wetland areas, and riparian buffers. Another strategy is to convert excess impervious area, such as wide swathes of concrete and asphalt, to landscape space. A typical project site could reduce 25 percent of its stormwater runoff if an equal 25 percent of impervious space was converted into pervious area. Transforming "gray space" it into "green space" not only reduces stormwater runoff volume,but it also provides room for additional trees and plants, beautifying the community.

For example, Figures 4-1 and 4-2 illustrate how an underused portion of a street can be redesigned to add landscape area along the street frontage. Figure 4-2: Same commercial street retrofitted with stormwater swale, bike lane, additional conventional landscaping, and street trees.



Figure 4-1: A typical low-density commercial street in Covington, Kentucky.



Figure 4-2: Same commercial street frontage retrofitted with stormwater swale, bike lane, additional conventional landscaping and street trees.



Figure 4-3: A green roof demonstration project at the Sanitation District No. I headquarters in Fort Wright, Kentucky.

Green roofs, also called "eco-roofs" or "living roofs," are living landscape systems that are designed to intercept rain as it falls on building rooftops. Water that normally runs off the roof and into a sewer system is absorbed by soils and plants on the roof or evaporates. The water that does run off the surface takes longer to do so and may be treated in a rain garden or used in the building in a graywater system (a system that collects nonpotable water for use in landscaping and irrigation). Green roofs have the added benefit of insulating buildings.

Green roofs can thrive on flat or sloped roofs, residential or commercial buildings, and small or large building footprints. A green roof can host a thin and simple palette of plants or thick, intensely planted rooftop landscapes.

Good Places for Green Roofs:

- Dense areas where land value is at a premium
- Large industrial buildings
- Office buildings
- Homes and garages
- In retrofit projects where building structure can support the added weight

Additional Benefits:

- Decrease heating and cooling costs by insulating and shading buildings
- Help reduce the urban heat island effect
- Provide wildlife habitat

There are two types of green roofs: extensive and intensive

Extensive green roofs are lightweight vegetated systems consisting of low-profile grasses, sedums, and/or wildflowers growing in a 3 to 5-inch thick soil medium (Figure 4-4).

Intensive green roofs have a minimum 5-inch depth soil profile and typically include a larger variety of plants and trees (Figure 4-5). Intensive green roofs can be elaborately designed and include large shrubs and trees, depending on the soil depth. These green roofs are required to be structurally sound to account for the additional weight from soil, plant, and water retention.

Both intensive and extensive green roof systems require installation of specialized soil media, drainage mats and overflow systems, and a waterproofing membrane.

A green roof's ability to manage stormwater runoff depends on its vegetation and the type and thickness of the soil mixture. The city of Portland, Oregon has reported that a green roof can capture and transpire 10 to 100 percent of the rainfall landing on the roof.

Green roofs reduce rooftop temperatures, decrease heating and cooling costs, help reduce the urban heat island effect, provide wildlife habitat, and can make buildings more attractive. In more densely developed areas where land value is at a premium, they also can provide additional green spaces for people to enjoy. Green roofs also work well in industrial uses where building footprints account for a large amount of impervious surface, and it is difficult to find enough land to manage stormwater on the ground.

Retrofitting conventional roofs with green roofs is possible, but it is necessary to determine whether the structure can accept the additional loading. The structural reinforcement needed for green roofs and the waterproof membrane are typically the highest costs in installing a green roof.



SOURCE: AMERICAN HYDROTECH, INC

Figure 4-4: Typical profile for an extensive green roof system.



Figure 4-5: Typical profile for an intensive green roof system.



Figure 4-6: Pervious paving used in the parking zone on a residential street in Portland, Oregon.

Pervious paving systems provide the structural integrity needed for cars, trucks, and high traffic pedestrian areas, while allowing water to drain through the paving system and into soils below. There is a range of pervious paving types, from those that look most like traditional paving, such as pervious asphalt and concrete, to those that are indistinguishable from lawn, such as structural grass-paving systems.

Pervious paving should be limited to those locations in Northern Kentucky with well draining soils. Locations with poorly draining soils would require an underdrain system that would slow the water somewhat, but would not necessarily reduce overall volume.

Good Places for Using Pervious Paving:

- Streets
- Parking lots
- Parking strips
- Alleys
- Patios

Additional Benefits:

- Can be safer than traditional paving because puddles are less likely to accumulate
- Provide aesthetic appeal
- Define a distinctive community character
- Delineate parking areas
- Calm traffic

Pervious Paving



Figure 4-7: Pervious concrete/asphalt.



Figure 4-8: Pervious concrete unit pavers.



Figure 4-9: Reinforced gravel paving.



Figure 4-10: Reinforced grass paving.



Figure 4-11: The difference between drainage on pervious asphalt and impervious asphalt is evident in this



photo.

Figure 4-12: This residential driveway uses pervious pavers in San Mateo County, California.



Figure 4-13: A plastic grid system filled with gravel provides the structural strength to support a vehicle.



Figure 4-14: Reinforced grass paving allows water to pass through the grass' root zone and into the underlying soil while still maintaining a hard surface for vehicular travel.



Figure 4-15: Pervious concrete allows water to pass through pore spaces in the aggregate.



Figure 4-16: Pervious concrete's light color helps reflect heat rather than absorb it.

Pervious Asphalt and Concrete:

Pervious asphalt and concrete production is similar to that of standard asphalt and concrete; the main difference is that the fines – the finergrained sediments that typically fill the pores between the larger aggregates - are left out of the aggregate added to the mixture. This leaves small pore spaces in the concrete that allow water to drain through the surface.

Pervious paving reduces the accumulation of puddles. In snowy conditions, pervious paving allows melted snow and ice to drain and the surface to dry faster, so there is less danger of re-freezing. Pervious paving has been successfully used on interstates and other limited-access roads because there are no turning vehicles.

When installing pervious asphalt and concrete, the subgrade must be properly prepared and the surface poured correctly. Where pervious asphalt and concretes fail, it is usually due to incorrect installation.



Figure 4-17: Pervious asphalt in the parking stalls at the Sanitation District No. I headquarters.

Any pavers can create a porous surface if there are spaces between them that are filled with sand or other aggregate that allows water to drain. Interlocking concrete unit pavers are designed for stormwater management and allow water to pass through joint gaps that are filled with sand or gravel and infiltrate into a thick gravel sub-grade. This system is widely applicable to both small and large paving applications and allows a small section to be removed when repairs are needed.

Reinforced Gravel Paving:

A gravel paving system uses gravel without the fines and a structure that helps provide support and create a rigid surface. Gravel can be a viable alternative to a traditional paved surface in areas of lower use that need a rigid surface.

Reinforced Grass Paving:

In the right situations, grass paving, or other hybrids between paving and planting, could be an option. Reinforced grass paving provides structural support but also allows some plants to grow and water to soak through into the soil. Grass paving cannot always be used interchangeably with standard asphalt or concrete, but it may be appropriate in lowtraffic areas.



Figure 4-18: Pervious pavers in a parking lot. Any overflow from the pervious pavers drains into a swale.



Figure 4-19: A close-up view of gravel paving within a reinforced plastic grid system.



Figure 4-20: Grass paving installed in a residential driveway.



Figure 4-21: Residential rain barrels used for summertime irrigation.

Rainwater harvesting has been used for thousands of years. It involves the capture of stormwater runoff from rooftops into containers for later use. This effectively slows and filters runoff before it reaches the drainage system. Today, in developed countries where drinking water is plentiful from the tap, rainwater harvesting captures rainfall primarily for non-potable uses such as supplemental irrigation, flushing toilets, car washing, and clothes washing. Rainwater harvesting is a viable method of managing stormwater runoff volume in areas in Northern Kentucky with poorly draining soils where infiltration is difficult.

Harvesting rainwater can be used at various scales: from households harvesting water for personal use in a rain barrel to larger commercial applications where water is captured for irrigation (see Figures 4-22 to 4-24). Systems can be as simple as disconnecting a residential downspout and directing the water to a rain barrel.

Good Places for Rainwater Harvesting:

- Large industrial buildings
- Office buildings
- Homes and garages

Additional Benefits:

- Water can be used for non-potable purposes, which leaves more water in public reservoirs to fill drinking water needs
- Systems can be artfully designed in concert with the building's architecture (see Figure 4-24)
- Systems can be a good educational tool to teach about watersheds

Rainwater Harvesting



Figure 4-22: Rainwater cisterns can come in all shapes and sizes.



Figure 4-23: Simple residential rain barrels are commonly used to capture and reuse rainwater for irrigation during dry periods.



Figure 4-24: This new LEED-certified building in Little Rock, Arkansas, included a large cistern in the interior stairwell of the building.



Figure 4-25: A new residential street incorporates a stormwater swale to collect stormwater runoff in Seattle, Washington.

Swales are long, narrow, gently-sloping vegetated depressions in the landscape. They are primarily used to move stormwater runoff on the landscape surface. As water flows through a swale, plants and soils slow its flow, allowing sediments and pollutants to settle out. Some water soaks into the soil and is absorbed by plants or infiltrates into the ground if native soils are well drained. The water that continues to flow downstream travels more slowly than it would through pipes in a traditional storm drainage system. Swales can be planted with a variety of plants, ranging from turf grass or a simple palate of grasses, sedges, and rushes, to a mixture of trees, shrubs, and groundcovers.

Swales are best implemented in areas of continuous landscape. A longer continuous swale allows more time for filtering to occur. Rural roads, arterial streets, and medians commonly offer this type of uninterrupted linear space. New subdivisions and parking lots can also offer good opportunities for swale design. Stormwater swales are relatively inexpensive, simple to construct, and widely accepted as a stormwater management strategy.

Good Places for Swales:

- Subdivisions
- Arterial streets
- Parking lots

Potential Retrofit Opportunities:

- Rural roads
- Parking lots
- Between buildings
- Planting strips

Additional Benefits:

• Attractive neighborhood amenity

Stormwater Swales





Figure 4-26: Key Design Considerations for a Stormwater Swale





Figure 4-27: A residential street with a stormwater swale.



NEVUE NGAN ASSOCIATES

Figure 4-28: A potential residential street swale opportunity in existing planting strip. Dashed lines show where a vegetated swale could be added.



Figure 4-29: An elementary school parking lot with a stormwater swale.

Swales and Streets

On a new street:

The long and linear character of streets can accommodate a swale's need for long uninterrupted stretches of landscape. Often streets have long stretches of right-of-way that is underused.

On an existing street:

- Look for long, unplanted, unused median strips or planting strips between the sidewalk and the street.
- Can turn lanes be removed, travel lanes moved to center, and swales added on sides?
- Is there a way to move that water on the surface rather than in a pipe?
- Can travel lanes on a particular street be narrowed?
- Does a street effectively use on-street parking, or can that extra impervious area be consolidated into swales? Can parking be moved to one side and a swale be placed on the other side?

Swales and Parking Lots

In a new parking lot:

Parking lots are a great fit for swales. Long drive aisles lend themselves well to the continuous spaces swales need. There are many creative ways to include swales in parking lots. For example, shorter parking stalls can yield a few extra feet of area, especially when a high number of parking spaces are required by code.

In an existing parking lot:

Often parking lots can be retrofitted without losing any parking spaces. It may not always be obvious how a parking lot might be retrofitted; look for:

- Parking lots with very long stalls;
- Wider than necessary travel lanes; or
- Angled parking with unused space in front of or behind each space.

Swales and Buildings

Near a new building:

Swales can treat stormwater runoff captured from buildings. An important design consideration is getting water away from the building foundation and lining swales to prevent foundation damage. Usually a minimum 10foot clearance from the building is required.



Figure 4-30: These parking spaces could be made just a few feet shorter to provide room for swales between rows of parked cars.



Figure 4-31: This stormwater swale at the Sanitation District No. 1 of Northern Kentucky headquarters collects runoff from the building's rooftop.



Figure 4-32: Stormwater planters are used to infiltrate stormwater runoff on a downtown street in Portland, Oregon.

Planters are long, narrow, often rectangular landscaped areas contained within vertical walls and with flat, unsloped bottoms. Planters slow the flow of water and absorb water into plants and soils, reducing the volume and intensity of water flowing downstream. Infiltration planters infiltrate stormwater, while flow-through planters absorb only as much water as they are designed to hold within their walls.

Planters are best used where space is limited or where the cleaner look of a clearly defined rain garden is desirable. Flow-through planters are a viable alternative when infiltration is not possible, such as close to building foundations or in areas of poorly drained soils as found in areas of Northern Kentucky. Planters can store more water than swales because they are often deeper and have vertical side walls that provide additional capacity compared to side slopes. Water flows into the planter, absorbs into the topsoil, fills to a predetermined overflow elevation, and overflows into the overflow system provided.

Good Places for Planters:

- Urban areas
- Street furnishing zones
- Adjacent to buildings
- Parking lots

Potential Retrofit Opportunities:

- Near condominiums
- Street furnishing zones
- Between buildings

Additional Benefits:

- Buffer between street and sidewalk calms traffic and makes pedestrians feel safer
- Beautifies urban spaces with trees and plants

Stormwater Planters



Figure 4-33: Key Design Considerations for a Stormwater Planter

1	Depth:		Maximum depth of 8 inches						
2	Side Slopes:		None - vertical						
3	Bottom Width: Plants - Bottom:		Flat; sealed in flow-through planter, open in infiltration planter						
4			Wet-tolerant rushes, sedges, shrubs, and tree						
5	Longitudinal Slo	ope:	Up to 6 %. If hillside is sloped more than 6% several planters can be terraced						
Not shown:									
Check Dams: At leas Trees: In bott Maintenance: Keep e correct event;			t I check dam for every 6 inches of vertical drop maximum om of planter, drought tolerant and wet tolerant ntry and exit points clear of debris; ensure check dams retain water depth with no erosion or standing water 48 hours after rain weed and trim plants semi-annually						



Figure 4-34: An urban street infiltration planter.



Figure 4-35: Planters can be retrofitted on urban streets with overly wide sidewalk zones. Dashed lines show where a planter could be added.



Figure 4-36: A narrow stormwater planter on the edge of a parking lot.

Planters and Streets

On a new street:

Planters take up less space than other rain garden strategies and therefore are a good candidate for urban settings where parking, signs, and other street furnishings vie for valuable real estate.

On an existing street:

Planters are commonly used to retrofit dense urban streets because they can treat a lot of water in a relatively small footprint, and fit into places where traditional rain gardens wouldn't fit. Look for:

- Dense areas where parking is critical; or
- Furnishing zones with extra space and sidewalk areas that are wider than necessary.

Planters and Parking Lots

In a new parking lot:

Planters can be designed to take the place of one parking spot. Water can be designed to flow into one, overflow, and flow across the parking lot surface and into the next planter.

In an existing parking lot:

Planters take up less space than swales and thus may be a better choice in parking lots where less space is available. Look for:

- Parking lots with very long stalls;
- Overly wide travel lanes; or
- Angled or heado-in parking with unused space in front of each space.

Planters and Buildings

In a new building:

Flow-through and infiltration planters can be designed to fit the architecture of a building and treat its runoff. They offer many opportunities for artistic expression through the design of scuppers and interesting gutters.

In an existing building:

Flow-through planters are a good way to 'freshen up'' an old foundation planting. What is required is the ability to dig a deep enough hole next to the building to be able to line the planter to avoid seepage into the building's foundation (see Appendix M for methods to protect a building's foundation). Look for:

- Old foundation plantings; or
- Leftover spaces between buildings and parking lots.



Figure 4-37: A stormwater planter next to a multifamily complex.



Figure 4-38: A stormwater planter accepts stormwater runoff from a fast food restaurant's rooftop.



Figure 4-39: An infiltration garden adjacent to an elementary school in Portland, Oregon.

Infiltration gardens are shallow, vegetated depressions in the landscape. Like swales, they typically have side slopes and flat bottoms. They can be any size or shape and are often molded to fit in "leftover" landscape spaces in parking lots, at intersections with diagonal streets, or in underused areas around buildings. They can be designed as one connected space, rectilinear or rounded, and are often as wide as they are long.

As the name suggests, infiltration gardens infiltrate stormwater and therefore are suitable primarily in locations with well-draining soil. Although infiltration gardens have similarities with swales and planters, they are categorized as a separate strategy based on the spaces in which they fit. Their primary advantage is their versatility in size and shape.

Good Places for Infiltration Gardens:

- Parking lots
- Awkward street intersections
- Adjacent to buildings
- Under-utilized spaces

Additional Benefits:

- Beautifies and softens parking lots and streets by adding plants
- Courtyards; or
- Garden areas that can be redesigned to accommodate stormwater runoff




Figure 4-40: Key Design Considerations for an Infiltration Garden

	Depth:	Maximum depth of 8 inches
2	Side slopes:	Can be vertical, or have side slopes
3	Bottom Width:	Flat, open to infiltrate into native soil
4	Plants - Side Slopes:	Drought-tolerant ground covers and shrubs, 80% evergreen
5	Plants - Bottom:	Wet-tolerant rushes, sedges, shrubs, and trees
6	Slope:	None - used to pond and infiltrate water
<u>Not sł</u> Check Trees: Mainte	nown: Dams: Used not i In bo enance: Keep come even	d to promote ponding of water and aid in grading if facility is n a flat location ottom of infiltration garden, drought tolerant and wet tolerant o entry and exit points clear of debris; ensure check dams retain ect water depth with no erosion or standing water 48 hours after rain t; weed and trim plants semi-annually



Figure 4-41: Large under-used areas of asphalt can easily be converted into infiltration gardens.



Figure 4-42: A triangle-shaped infiltration garden retrofitted along a busy arterial street.



Figure 4-43: An infiltration garden retrofitted within a middle school's parking lot.

Infiltration Gardens and Streets

On a new street:

In new design, infiltration gardens can be incorporated at street intersections, in the centers of roundabouts, or in central medians.

On an existing street:

industrial Many downtowns, areas. neighborhoods, and rural areas have large areas of unused or inefficiently used pavement on streets and parking lots that could be converted to infiltration gardens. Look for:

- Unused or inefficiently used pavement; or
- Lawn areas at street intersections.

Infiltration Gardens and Parking Lots

In a new parking lot:

Infiltration gardens can be used in parking lots requiring more treatment area than swales and planters can provide. Infiltration gardens are also a good option if there is a focal area that could be beautified and be used as an interpretive area.

In an existing parking lot:

Parking lots sometimes have more spaces than necessary, and those spaces can be taken over for infiltration gardens. Look for:

- Parking lots with excess spaces;
- Parking lots with underused landscaped or asphalt areas nearby; or
- Parking lots with very long stalls or wider than necessary travel lanes that could be redesigned to create space for an infiltration garden.

Infiltration Gardens and Buildings

Near a new building:

Imagination is the limit to the ways in which infiltration gardens can complement building architecture. Many opportunities exist for integrating infiltration gardens with rainabsorbing footprint strategies such as rainwater harvesting.

Near an existing building:

Infiltration gardens can be designed as an amenity to existing buildings by redesigning surrounding landscapes or by reclaiming unused paved areas near buildings. Look for:

- Unused space in industrial areas;
- Schools, churches, and other public buildings with excess space;
- Spaces between buildings.



Figure 4-44: An infiltration garden installed within an apartment complex in Portland, Oregon.



Figure 4-45: A large infiltration garden accepts stormwater runoff from a middle school's rooftop.



Figure 4-46: Stormwater curb extensions used on a residential street in Portland, Oregon.

Conventional curb extensions, also known as curb bulb-outs, chokers, or chicanes, have been used for decades to protect pedestrians and help calm traffic. Communities can add a stormwater benefit by allowing water to flow into a curb extension. Within the curb extension boundary, they share the characteristics of swales, planters, or infiltration gardens, but are discussed independently due to their unique street application.

Curb extensions intercept water running along a curb and gutter before it reaches the catch basin. Plants slow and filter rainwater flowing through curb extensions so that it moves more slowly than it would in a traditional storm sewer pipe system. Water flowing through curb extensions has a chance to soak into the ground where soil permits before excess water flows back out to the curb and into a catch basin. Using curb extensions is particularly advantageous in retrofits because they can often be added to existing streets with minimal disturbance. The relatively small footprint of stormwater curb extensions allows for an efficient stormwater management system, and hence they often perform well at a relatively low implementation cost.

Good Places for Curb Extensions:

• At entry of slower residential street from a busier street to calm traffic

Additional Benefits:

- Beautifies the street
- Creates shorter crossing distances for pedestrians and calm traffic



Figure 4-47: Key Design Considerations for a Stormwater Curb Extension

1	Depth:	Maximum depth of 8 inches		
2	Side Slopes:	Can have vertical walls or side slopes, depending on street context		
3	Bottom Width:	3 feet wide minimum, rounded or flat; can be sealed, as in a flow- through planter, or open as shown		
4	Plants - Side Slope	s: Drought-tolerant ground covers and shrubs, 80% evergreen		
5	Plants - Bottom:	Wet-tolerant rushes, sedges, shrubs, and trees		
6	Longitudinal Slope	: Up to 6%. If hillside is sloped more than 6%, several planters can be terraced		
Not shown:				
Check Dams: Used t not in Frees: In bott Maintenance: Keep e correct event;		I to promote ponding of water and aid in grading if facility is in a flat location of curb extension, drought tolerant and wet tolerant entry and exit points clear of debris; ensure check dams retain ect water depth with no erosion or standing water 48 hours after rain t; weed and trim plants semi-annually		

Stormwater Curb Extensions





New perimeter Figure 4-49: Curb extensions can provide stormwater management opportunities and safer crossings for pedestrians.

Figure 4-50: Curb extensions can fit nearly anywhere and help calm traffic to protect pedestrians.

typically flows within a stormwater curb extension.



Figure 4-51: Stormwater curb extensions commonly have a symmetrical orientation at intersections.



Figure 4-54: Accessible pedestrian ramps can also be integrated into the design of stormwater curb extensions.



Figure 4-52: At the mid-block of a street, stormwater curb extensions can have be symmetrical or staggered orientation.



Figure 4-55: A pair of stormwater curb extensions installed along a neighborhood street.



Figure 4-53: When streets connect at odd angles, stormwater curb extensions can help create safer pedestrian crossings as well as manage stormwater runoff.



Figure 4-56: A large stormwater curb extension retrofit along a busy arterial street.



Figure 4-57: Roof downspouts can be easily disconnected and allow runoff to flow into surrounding landscaped areas.

Downspout disconnection is one of the simplest ways that a homeowner, even one with a small yard, can help with stormwater management. Most gutters and downspouts are connected to the public storm sewer or a combined sewer system. Disconnecting the downspouts and directing runoff onto lawn areas slows and filters rainwater and lets it absorb into soils locally instead of sending it in a pipe to stormwater treatment downstream.

Downspout disconnection can be easily integrated with rainwater harvesting (see Section 4.3 for more details about rainwater harvesting).

Good Places for Downspout Disconnection

- Single-family homes
- Small multifamily buildings
- Small office buildings

Additional Benefits:

- Educates homeowners about watershed system
- Is a simple action that almost everyone can take to contribute to comprehensive stormwater management strategies in a community

Downspout Disconnection



Figure 4-58: An office building in Covington has disconnected roof downspouts that allow water to flow into a landscaped area.

Ė



Figure 4-59: A residential example of downspout disconnection in Covington.



Figure 4-60: An example of allowing water to cascade from a building rooftop into a landscaped area.

Chapter 4 introduced the green infrastructure strategies for stormwater management and basic characteristics of each strategy. This chapter explores opportunities for applying the strategies in street, parking lot, and building conditions found in Northern Kentucky. The example plans, diagrams, and sketches shown in the following section demonstrate a variety of ways that the toolbox strategies could be applied.

These examples are meant to give a taste of what is possible for both new and retrofit construction. Local decision-makers, residents, designers, developers, and other stakeholders will decide which strategies work best for their goals and site conditions (i.e., as soil type and topography). Northern Kentucky has a range of soil conditions from very well-draining, loamy soils to poorly-draining, clay soils. These conditions need to be taken into account in the selection and design of a particular strategy.

Several "before and after" sketches show the potential for green streets, parking lots, and building applications in Northern Kentucky. The majority of drawings are based on sites the team saw during its April 2008 visit to Covington, and some are from work in other areas of the country. All though represent similar opportunities that exist throughout Northern Kentucky. The goal of illustrating multiple site strategies is to give communities a broad range of site-scale design applications that could be used throughout the region.



Figure 5-1: Residential streets offer some of the best opportunities to incorporate rain garden designs.



Figure 5-2: Parking lots can be designed or redesigned to maximize landscape area for stormwater management.



Figure 5-3: Landscape areas next to buildings can be converted into rain gardens as well.

Residential Streets



Residential streets often offer the greatest potential for building green streets. Typically, most new developments use conventional engineering approaches to manage street runoff. Multiple green street opportunities exist for new construction and for retrofitting existing streets to recapture some of the attractive character of the older streets found in cities like Covington. This section illustrates possibilities for managing stormwater runoff from residential streets in Northern Kentucky.

Figure 5-4: A residential street within an established neighborhood in Northern Kentucky.



Figure 5-5: Conventional Low-Density Residential Street-Plan View

Using Stormwater Curb Extensions

Many streets in Northern Kentucky could be retroffited with stormwater curb extensions that could contain rain gardens while not affecting existing trees. This residential street example illustrates how stormwater curb extensions can be easily retrofitted alongside the existing curb

line. Runoff from the street can simply enter these landscape areas and overflow into the existing drain inlets. Because this street has a lot of unused on-street parking, installing curb extensions would not take away needed parking. With the new stormwater curb extensions and street trees in place, the narrower street provides a more aesthetically pleasing and potentially safer traffic environment.



Figure 5-6: EXISTING: A typical low-density residential street in Covington.



Figure 5-7: RETROFIT OPPORTUNITY: Same residential street retrofitted with stormwater curb extensions.

Residential Streets

43



Figure 5-8: Stormwater Curb Extension at Intersection-Plan View



Figure 5-9: A pair of stormwater curb extensions used in a residential street's parking zone in Portland, Oregon.

Mid-block Stormwater Curb Extension Applications

The street in Figure 5-10 illustrates an opportunity to use stormwater curb extensions mid-block. Mid-block curb extensions can be designed in many shapes and layouts. Figures 5-12 and 5-13 show stormwater curb extensions in either a symmetrical or staggered pattern to calm traffic. Stormwater curb extensions do not have to be paired on both sides of the street. Figure 5-11 shows a midblock curb extension on only one side of the street to accommodate existing driveways on the other side. Pervious paving on the driveway side of the street could complement the mid-block curb extension and better manage the street's stormwater runoff.



Figure 5-10: EXISTING: A typical, narrow, low-density residential street in San Mateo County, California.



Figure 5-11: RETROFIT OPPORTUNITY: Same residential street retrofitted with mid-block stormwater curb extensions as well as additional street trees.

Residential Streets



Figure 5-12: Mid-Block Stormwater Curb Extension (Staggered Layout)-Plan



Figure 5-13: Mid-Block Stormwater Curb Extension (Symmetrical Layout)-Plan

Options for New Development

The street shown in Figure 5-14 has lawn in planting strips between the street and the sidewalks. The design could have substituted swales for lawn in the planting strips, with a curbless condition to allow water to sheet flow into the swales (see Figure 5-15). These design changes could provide significant stormwater management area, reducing the need for a larger facility to treat all the runoff from this development in one location. Figure 5-16 and Figure 5-17 show additional options for using swales depending on how streets are crowned (See Appendix C).



Figure 5-14 EXISTING: A new residential street in Lewes, Delaware.





Figure 5-16: Swale on One Side of Street, Parking on Other Side-Plan View View



Figure 5-17: Side Swales and Median Swale (No On-Street Parking)-Plan View

Pervious Paving in the Parking Zone

Pervious pavers in the parking lane can give the illusion of a narrower street and therefore help calm traffic. They convert impervious surface to allow stormwater to absorb into the ground, reducing the amount of runoff, without any loss of parking on the street.



Figure 5-18: EXISTING: A typical urban residential street in Covington,.



Figure 5-19: RETROFIT OPPORTUNITY: Same residential street retrofitted with pervious paving in the parking zone of the street.

Residential Streets



Figure 5-20: Pervious Paving in Parking Zone-Plan View



Figure 5-21: Pervious paving used in a residential street's parking zone. Notice the visual "narrowing" of the street.

Residential Alley Swales

Putting garages behind homes makes the street more pedestrian friendly, and the architectural detail of the home is no longer dominated by a front-entry garage. Providing alley access and eliminating the driveways at the front of homes not only enhances the overall streetscape, but also allows a more contiguous landscape area along the street frontage and front yards.

The example in Figure 5-23 transforms the alley in Figure 5-22 by draining water to the sides into narrow swales. The example shows a crowned alley, draining to both sides. An alternative would be to drain the whole alley to a swale on one side. This example shows a curbless condition, with sheet-flow of stormwater into the swale. The swale is shallow, and the street has a low traffic volume. Access across the swale for cars and pedestrians can be provided by either a culvert or small bridge.



Figure 5-22: EXISTING: An alley in a new residential development in Sussex County, Delaware.



Figure 5-23: RETROFIT OPPORTUNITY: Same residential alley retrofitted with side stormwater swales.



Figure 5-24: EXISTING: A commercial main street example in Northern Kentucky.

Many of the historic main streets in Covington and other cities of Northern Kentucky have a wonderful community-oriented and smalltown character that the residents cherish. However, like most urban areas in the United States, it can be difficult to find available space for stormwater management and also accommodate space for parking, bikes, pedestrians, street trees, lighting, etc. There are, however, several design options cities could consider when looking to integrate stormwater in its most active streets. The following pages offer examples of how stormwater planters, swales, curb extensions, infiltration gardens, and pervious paving could be integrated into town center streets. These design options could be used in either new construction or retrofits and can fit beautifully with the character of the streetscape.



Figure 5-25: Conventional Commercial Main Street-Plan View

Main Street With Stormwater Planters

This design adds stormwater planters to be added to the furnishing zone while retaining on-street parking. A band of paving, which can be pervious paving or another paving material, allows access to cars parked on the street. This design links a series of flow-through planters or infiltration planters. Water flows into the first one; when it fills up, water can flow back out to the street gutter and into the next planter, and so on. If any stormwater overflows at the end, after the last planter, it flows into the existing catch basin. An advantage of using planters in downtown areas is that they treat a given amount of water in tighter spaces because of their vertical walls. In addition, they add greenery and make the streetscape more appealing.



Figure 5-26: EXISTING: A commercial street in Covington with on-street parking.



Figure 5-27: RETROFIT OPPORTUNITY: Same commercial street retrofitted with a series of stormwater planters.

Commercial Main Streets



Figure 5-28: Stormwater Planters With On-Street Parking-Plan View



Figure 5-29: Stormwater planters used along a downtown street. Space should be allocated for people to get in and out of their vehicles and access the sidewalk.

5.2

Parking on One Side, Stormwater on the Other

This example shows stormwater planters on a two- or four-lane road without onstreet parking. The underused travel lane next to the sidewalk has been consolidated into a rain garden and a bike lane. The stormwater planter or swale can be located right up to the edge of the curb because there is no on-street parking. Figure 5-31 illustrates a curbless condition that allows runoff to flow directly into the swale. Bollards are used to separate the bike lane from the swale.



Figure 5-30: EXISTING: An urban street in Covington.



Figure 5-31: RETROFIT OPPORTUNITY: Same street without one traffic lane and retrofitted with a "curbless" street, vegetated swale, and bike lane.

Commercial Main Streets



Figure 5-32: Curbless Street With a Vegetated Swale/Planter on One Side-Plan



Figure 5-33: Curbless Street With a Vegetated Swale/Planter on One Side-Cross Section

"Green Gutter" Narrow Planter

As with previous examples, the underused portion of the street in Figure 5-35 is given a stormwater management purpose that in turn creates a more attractive streetscape. This design incorporates a landscape strip on the sidewalk and a three-foot wide strip of paved area converted to a narrow, shallow planter called a "green gutter."



Figure 5-34: EXISTING: An urban street in Covington.



Figure 5-35: RETROFIT OPPORTUNITY: Same street retrofitted with a "green gutter."

Commercial Main Streets



Figure 5-36: Commercial Street Green Gutter-Plan View



Figure 5-37: Commercial Street Green Gutter-Section View

Curb Extensions and Pervious Paving in Parallel Parking Zone

The curb extensions shown for residential streets in Section 5.1 can also be adapted to commercial streets. Figure 5-39 illustrates a curb extension with a rain garden planter that is about the size of one parking space. The planters can be built mid-block and serve as street tree planting pits if the sidewalk are too narrow to accommodate street trees.



Figure 5-38: EXISTING: A typical commercial main street with on-street parking in San Mateo County, California.



Figure 5-39: RETROFIT OPPORTUNITY: Same commercial street with pervious paving in the parking zone and stormwater curb extensions.

Commercial Main Streets



Figure 5-40: Combination of Pervious Paving and Curb Extensions in Parking Zone-Plan



Figure 5-41: This urban street in Portland, Oregon uses pervious paving in its parking zone and could have provided more stormwater management by adding stormwater curb extensions.

Angled Parking Solutions

Angled parking along commercial main streets is common in cities in Northern Kentucky. One green street design scenario consolidates one or more parking spaces into a curb extension. Converting angled parking spaces into curb extensions can add more landscaping to the street which could also make storefronts more attractive.



Figure 5-42: EXISTING: A typical commercial main street with angled parking in San Mateo County, California.



Figure 5-43: RETROFIT OPPORTUNITY: Same commercial street with two angled parking stalls converted into stormwater curb extensions.

Commercial Main Streets



Figure 5-44: Angled Parking Curb Extensions-Plan ViewView



Figure 5-45: Angled Parking Curb Extensions-Cross Section

Converting "Gray Space" into "Green Space"

This design illustrates how a more efficient street design can create space for rain gardens. Figure 5-46 shows a streetscape with an oversized travel lane and sidewalk andno street trees or landscaping. The retrofit in Figure 5-47 provides a bike lane, a swale, a landscape strip and a narrow buffer between the sidewalk and the adjacent parking lot.



Figure 5-46: EXISTING: A typical urban street in Northern Kentucky with no on-street parking. The travel lane and sidewalk are twice as wide as needed.



Figure 5-47: RETROFIT OPPORTUNITY: Same street retrofitted with a bike lane, stormwater swale, and additional landscaping and street trees.

OURCE: NEVUE NGAN ASSOCIATES



Figure 5-48: EXISTING: An existing urban alley in downtown Covington.

An Urban Alley Retrofit

A variety of pervious paving options are available for retrofitting urban alleys with green infrastructure. This example uses pervious concrete with a distinctive serpentine valley gutter that collects any overflow runoff. Simply greening the space alongside buildings can make the alley a more attractive. Swales and planters can achieve this; however, the alley must have adequate space to incorporate these elements with the daily transportation requirements.



Figure 5-49: RETROFIT OPPORTUNITY: Same alley retrofitted with pervious concrete and an artistic valley gutter to convey overflow.



Figure 5-50: EXISTING: A multi-lane arterial street example in Northern Kentucky.

Many of Northern Kentucky's arterial streets have large landscape areas adjacent to the roadway. Even though some of these streets have grassy medians and side strips, many do not allow for stormwater management. Hence, retrofitting existing arterials to manage stormwater could help protect water quality. Like residential streets, arterial roadways are great street types for swales because they typically have long, linear stretches of uninterrupted space that could be used to manage stormwater. Some arterials may not have landscape space in place but

do have travel lanes or paved shoulders that could be narrowed to create space for swales. This space might also be used for sidewalks, on-street bike lanes, or landscape-separated bike greenways.

Examples in the following section illustrate ways that arterial streets can be built or retrofitted to provide both stormwater management and more transportation choices.



Figure 5-51: Conventional Highway/Arterial Street-Plan View

Four-Lane Arterial: Retrofit or New Construction

This four-lane arterial has enough room in the shoulder and utility zone to build a bike lane, sidewalk, safety buffer, and swale. The design can be modified to preserve the shoulder, if it is critical.



Figure 5-52: EXISTING: This arterial street in Lewes, Delaware has an extra wide shoulder that could be used more efficiently.



Figure 5-53: RETROFIT OPPORTUNITY: This retrofit example meets multiple goals by adding a bike lane that is buffered from the road, a sidewalk, and a stormwater swale.



Figure 5-54: EXISTING: A multi-lane boulevard with an extra wide sidewalk in Nashville, Tennessee.

Oversize Sidewalk Converted Into a Stormwater Swale

This example shows how a part of an overly wide sidewalk adjacent to an arterial could be reclaimed and used for a swale while still being safe and attractive for pedestrians.



Figure 5-55: RETROFIT OPPORTUNITY: Same street consolidates the wide sidewalk space for a stormwater swale and street trees along the boulevard.
Option for an Arterial Street With Multiple Swales

This is another example of how a typical four- or two-lane highway could be designed to not only manage stormwater runoff, but also allow for multiple transportation options, including biking and walking. On-street bike lanes can be used or, if there is adequate space, a separated bike path can provide more protection for bicyclists and pedestrians. Also, depending on the drainage pattern of the roadway, median grassy swales could also manage a portion of the road's runoff.



Figure 5-56: Stormwater side swale with bike lanes on arterial street in Oregon City, Oregon.



Figure 5-57: Side Swales on a Multi-Lane Arterial-Plan View



Figure 5-58: A typical parking lot in Northern Kentucky.

Previous sections of this handbook have described how designing sites such as parking lots efficiently can yield significant space for landscape areas. Even if landscape areas are not used for rain gardens, they remove impervious area and can be used for planting large canopy trees, native shrubs, and groundcovers. Pervious paving is widely accepted in parking lots and is particularly useful in small parking lots where space is tight, but generally most appropriate for areas with infiltrative soils. Stormwater swales are the most common rain garden strategy used in parking lots. Long, linear swales fit well in between rows of parking. Even curb extensions and infiltration gardens can be used in parking lots. As with street applications, rain gardens in parking lots should be carefully designed to ensure safe pedestrian circulation (see Appendix D). The following pages illustrate different rain garden strategies that could be used in parking lots throughout Northern Kentucky.



Figure 5-59: Conventional Parking Lot Conditions-Plan View

Parking Lot With Side Swale

The top consideration for green parking lot design is the grading of the parking lot and how the water flows into the rain gardens. It is best to sheet-flow the water across the surface of the lot and get it into swales or planters as soon as possible.

When grading a parking lot, remember that it doesn't take a large obstacle to redirect sheet-flow of water; even speed bumps can also be used for water diversion (see Appendix I).

The plan illustration in Figure 5-61 shows a parking lot with a side swale that separates the parking from the adjacent sidewalk.



Figure 5-60: A parking lot swale located at the Sanitation District No. I headquarters.



Figure 5-61: Vegetated Side Swale/Planter With 90-Degree Head-In Parking-Plan View

5.4

Side Swale in Parking Lot With Angled Parking

In this example, angled parking creates an unused space between the wheel stop and the edge of planter strip. This could easily be converted to a swale (or could have been designed as a swale initially). Planting trees would make this a more attractive sidewalk and would also intercept and absorb rainfall.



Figure 5-62: EXISTING: An angled parking lot example in Covington.



Figure 5-63: RETROFIT OPPORTUNITY: Same parking lot retrofitted with a stormwater swale/planter.

Parking Lots



Figure 5-64: Vegetated Side Swale/Planter With Angled Parking-Plan View



Figure 5-65: This parking lot with angled parking has a series of curb cuts that allow stormwater runoff to enter a landscaped area.

Center Median Stormwater Swale in a Parking Lot

This example illustrates how a swale can be incorporated between parking rows in larger parking lots. Shortening the length of the stalls creates space for landscaping to infiltrate stormwater and plant trees. Trees help cool the asphalt and reduce the urban heat island effect.



Figure 5-66: EXISTING: A parking lot at a high school in Covington.



Figure 5-67: RETROFIT OPPORTUNITY: Same parking lot retrofitted with a center median stormwater swale. Introducing this new landscaped area can help cool the parking lot surface and increase overall aesthetics.



Figure 5-68: Center Median Swale-Plan View



Figure 5-69: This parking lot in Portland, Oregon was built with a center median stormwater swale.



Figure 5-70: This infiltration garden captures, slows, absorbs, and filters runoff from a nearby street and parking lot.

Parking Lot Infiltration Garden

Often times larger underused asphalt or landscaped space is located at the periphery of parking lots. The design example illustrated in Figure 5-70 shows a parking lot with stormwater flowing to a large infiltration garden. As with the previous swale examples, the parking lot is graded so that water flows into a valley gutter, which carries runoff to a infiltration garden.



Figure 5-71: Parking Lot Infiltration Garden-Plan View

Parking Lot With Pervious Paving and Stormwater Planters

This example shows a parking lot using a combination of stormwater management strategies. The pervious pavers capture and infiltrate some runoff. Any overflow from the pervious pavers sheet-flows over a slightly graded slope to stormwater planters at the end of the parking bay.



Figure 5-72: This parking lot manages a portion of its stormwater runoff with multiple stormwater planters.



Figure 5-73: Parking Lot With Pervious Paving and Stormwater Planters-Plan View



Figure 5-74: A green roof project in Washington, D.C.



Figure 5-75: An infiltration planter along a building in Portland, Oregon manages stormwater runoff.

Northern Kentucky has many different building types, ranging from historic town center buildings in Covington and Newport, to newer commercial centers and residential communities. Stormwater management techniques include green roofs, rainwater harvesting, flow-through planter systems, and downspout disconnection that redirects stormwater to rain gardens. Each strategy or combination of strategies depends on the building type and the amount of landscape space surrounding the building.

In most urban settings, the lack of surrounding landscape area may mean that the only feasible stormwater strategies might be green roofs or narrow flow-through planters. In some cases, green roofs can be cost prohibitive to implement, so planters (both infiltration and flow-through) might be the best option. Conversely, buildings in less dense situations have more stormwater management options because perimeter landscaping is often available.

This section illustrates some ideas to incorporate stormwater management can into building design.



Figure 5-76: Disconnected downspouts at a school site in Portland, Oregon convey water into nearby infiltration planters.

Buildings

Foundation Planting Converted into a Rain Garden

This example illustrates how existing foundation planting could be converted into a flow-through planter that would capture and filter water from the building's roof. Depending on the site conditions, planters and swales next to buildings can be flow-through or allow for infiltration.



Figure 5-77: EXISTING: A typical grocery store foundation planting in Northern Kentucky.



Figure 5-78: RETROFIT OPPORTUNITY: Same store retrofitted with a stormwater planter in the existing foundation planting space.

Small Roof To Green Roof

This example shows a typical rooftop on a school. Though this is a small roof, converting this space into a green roof helps capture and filter stormwater. It also better insulates the roof during winter cold and summer heat.



Figure 5-79: EXISTING: A small conventional roof at a high school in Northern Kentucky.



Figure 5-80: RETROFIT OPPORTUNITY: Same rooftop retrofitted with a small green roof. Capitalizing on small opportunities like this can help make a difference in mitigating stormwater runoff.

Buildings

OURCE: NEVUE NGAN ASSOCIATES

ASSOCIATES



Figure 5-81: EXISTING: Linear spaces between buildings, such as side yards, are a good opportunity for beautifying the yard and treating stormwater with a swale.

Residential Rain Garden

In this example, the homeowner has directed their roof downspouts to allow stormwater to enter the new rain garden. The result is a beautiful garden and better stormwater management.



Putting It All Together: Applying Green Infrastructure at the Regional and Neighborhood Scale in Northern Kentucky

This chapter outlines ideas for how Northern Kentuckycommunities might combine the range of green infrastructure strategies presented in this handbook to protect water quality and create vibrant, livable neighborhoods.

The technical assistance team explored as part of its planning and architectural design exercise four study sites in the city of Covington: the Riverfront, City Heights, Latonia Terrace, and the Retail Center. The location of each site is shown on the poster created for the project (Figure 6-3). For each site, the team focused on what was being heard from community members and stakeholders: address stormwater management issues but also create and revitalize streets and neighborhoods to help Northern Kentucky communities grow sustainably.

The design ideas are offered solely to engage the community's interest and curiosity and to provide a starting point for brainstorming potential solutions to Northern Kentucky's stormwater-related challenges. The sites have not been studied in detail, and the team recognizes that some options might not be feasible due to financial, political, or other constraints.



Figure 6-1: Implementing green infrastructure demonstration projects, such this green street in Portland, Oregon, is the next step for Northern Kentucky.





Figure 6-3: The technical assistance team looked at several opportunity sites around the Covington area to showcase how Northern Kentucky communities can apply green infrastructure strategies.

VAN METER WILLIAMS POLLAG

SOURCE:

The Riverfront site is located in downtown Covington, bounded by the Ohio River to the north, West 5th Street to the south, Madison Avenue to the east, and the Route 42/127 bridge approach to the west (see Figure 6-4). The majority of the site is currently occupied by a large, one-story office building used as a processing center by the Internal Revenue Service (IRS) and by several adjoining parking lots.

The design for the site is a compact, pedestrian-oriented, mixed-use development that integrates homes, office space, and retail space; provides open space and public access to the river; and incorporates stormwater treatment measures. The team relocated the IRS operations to two midrise office towers and consolidated parking into a multi-story parking garage with street-level retail storefronts to make the building more pedestrian-friendly. One or two additional mid-rise towers for homes or offices would be built along the river to allow more people to take advantage of the open views and easy access to the waterfront. The team envisioned a central open space in the form of a broad linear park running through the middle of the development and lined with residential buildings. The park would serve as a community gathering space for neighborhood residents and workers. The park would provide connection to the river, and, along with the streets, be designed to incorporate stormwater treatment measures such as vegetated swales, planters, and landscaped curb extensions.



Figure 6-4: A conceptual plan view of the Riverfront site near downtown Covington.

The Covington Housing Authority volunteered two of its residential properties as study sites for the design exercise. The first, City Heights, is approximately 1.5 miles south of downtown Covington. It is located on the top of a wooded hill roughly bounded by Highland Avenue to the north and Madison Avenue to the east and south. The site consists of 64 multi-family apartment buildings owned and operated by the Housing Authority.

The design team identified opportunities to use the site more efficiently, beautify the open space, and better connect the site with the surrounding neighborhoods, schools, and Madison Avenue. The team offered three development options:

Design Option I (Figure 6-7)

The first option is to redevelop the site, retaining the same number of units by replacing the existing buildings with three- to four-story structures, integrating market-rate residential units, and organizing the units around the communal open spaces and a new set of streets that incorporate stormwater treatment measures. Parking lots would be replaced with on-street parking or with podium parking in some of the new buildings. A stairway would connect to Latonia Terrace and Madison Avenue, and a new road would extend from Muse Drive to 26th Street to provide a new connection to the site.

Design Option 2 (Figure 6-8)

This option doubles the number of residential units on the site. The existing buildings would be replaced with new structures consisting of market-rate condominiums or mixed-income housing. This would entail selling the site to a private developer; the Housing Authority could use the proceeds to construct replacement units, either by redeveloping one or more of its other sites or acquiring and developing a new property. Like Option I, this option would also provide new streets and open



Figure 6-5: The existing conditions at the City Heights site in Covington.



Figure 6-6: A conceptual sketch of the City Heights Rose Garden accepting stormwater runoff as presented in Design Option 3.

space incorporating stormwater treatment measures and would establish new pedestrian and vehicular connections to the surrounding community.

Design Option 3 (Figure 6-9)

The third option would redevelop the site as a hilltop park serving the whole city with a complex of recreational facilities; including baseball and soccer fields, basketball and tennis courts, walking trails, community gardens, a stormwater rain garden, and buildings that could be used for community meetings and other special functions. Public-housing units would be relocated to new mixed-use development throughout the city.



TER WILLIAMS POLLACI

Figure 6-7: A conceptual plan view of Design Option 1.

DESIGN OPTION I KEY ELEMENTS: Replacement of existing residences, with the addition of market-rate residential units.

- Reconstruct all existing housing flats and townhouses.
- Organize housing around new streets and open spaces.
- Incorporate stormwater management into new streets and open spaces.
- Establish pedestrian and vehicular connections to Latonia Terrace and Madison Avenue to and to the high school.
- Replace residential parking lots with on-street parking.
- Increase density with three-story buildings.
- Add podium parking with three stories of residences above to use land efficiently.

City Heights



SOURCE: VAN METER WILLIAMS POULA

Figure 6-8: A conceptual plan view of Design Option 2.

DESIGN OPTION 2 KEY ELEMENTS: Mixed-income housing or private development 100% replacement plus 50-100% additional units.

- Double residential density with condominiums.
- Incorporate stormwater management in the construction of new streets and open space.
- Create a common, central open space.
- Add podium parking with courtyard, provide private open space, and three stories of residences above.



'AN METER WILLIAMS POLLACI

Figure 6-9: A conceptual plan view of Design Option 3.

DESIGN OPTION I KEY ELEMENTS: New city recreational park on hilltop. Housing relocated to new mixed-use development sites in Covington.

- Reconstruct, preserve, and protect hillsides and hilltops for stormwater management strategies, and connect with open space corridors to community below.
- Create common open space on the hilltop with athletic fields, basketball and tennis courts, and a rose garden and native plant garden.
- Site various community-oriented buildings to support the recreational park.

The second Housing Authority site is Latonia Terrace, a complex of 25 multi-family apartment buildings located just downhill from City Heights, along Madison Avenue. Much as under Option 2 for City Heights, this property would become a new mixed-income residential development, and the site would be redeveloped—including rebuilding the existing buildings—at twice the current residential density (see Figures 6-11 to 6-13).

For this site, Madison Avenue would be rebuilt as a green street, with stormwater planters, street trees, landscaped curb extensions, and parking lanes surfaced with pervious paving. An open space corridor extending downhill from City Heights would be maintained across the development and would continue across Madison Avenue to connect to undeveloped parcels on the east side of the street. The functions of this green corridor would be to convey hillside runoff to the lowlands and the rivers keeping the runoff out of the combined sewer, and to serve as a pedestrian connection between Madison Avenue and City Heights. Courtyards between the buildings would accommodate stormwater swales and planters that would accept stormwater runoff from adjacent impervious areas. Mature trees around the development would be retained, and ample landscaping, groundcover, and pervious surfaces would be provided throughout the site. Green roofs would capture rainfall on building rooftops. Stormwater planters would capture any runoff from building rooftops and overflow either into the stormwater swales or into cisterns located in the underground parking garages for later reuse for irrigation.



Figure 6-10: The existing conditions at the Latonia Terrace site in Covington, Kentucky.



Figure 6-11: A conceptual plan view of Latonia Terrace.

LATONIA TERRACE: New mixed-income residential development

- Double residential density.
- Replace existing Housing Authority housing and add new residences.
- Incorporate stormwater management.

Latonia Terrace



Figure 6-13: A view into the various stormwater management and site design features at the redesigned Latonia Terrace site.

The fourth site identified by the design team is roughly 2.5 miles south of downtown Covington. It is located along Winston Avenue, between West 38th Street to the north and Howard Litzler Road to the south (see Figure 6-14). The site has two strip malls set behind large, underused, parking lots. There is a smaller undeveloped parcel on the northwest corner of the site along the railroad. Across Winston Avenue is an older, established neighborhood of single-family homes.

This site offered the design team the opportunity to explore revitalizing an aging in-town commercial area through compact, pedestrian-oriented, mixed-use development. The team envisioned redeveloping the northern half of the site (between West 38th and West 43rd streets) with a well-integrated mix of residential, office, and retail space. The western side of Winston Avenue would be lined with four- to five-story buildings, with shops on the ground level and apartments or condos above. Behind them would be lower-rise townhouses, accessed by alleys, flanking a linear park. The site would be threaded with narrow, pedestrian-friendly streets and alleys featuring attractive streetscapes that accommodate stormwater treatment measures such as vegetated swales, pervious paving, and landscaped curb extensions. The currently undeveloped parcel would be turned into a neighborhood park. Both the neighborhood and linear parks would serve double duty as open space and as stormwater treatment areas for the surrounding streets, buildings, and parking lots.



Figure 6-14: A conceptual plan view of the Retail Center site in Covington.

In Conclusion

In recent years, new approaches to stormwater management have been adopted and implemented by communities across the nation. For some, this evolution in stormwater management reflects the need to meet water quality regulations while also improving the community's character. Northern Kentucky has taken an important step in responding to these challenges with the *Stormwater Management Handbook: Implementing Green Infrastructure in Northern Kentucky Communities.*

This handbook introduced what green infrastructure is and how it can be applied at the regional, neighborhood and site-level scale within Northern Kentucky. The handbook also illustrated just a few of the many strategies and opportunities to implement green infrastructure—in particular, retrofitting streets and parking lots to protect water quality and create vibrant, livable neighborhoods and attractive walkable streets.

То ensure the continued economic development of Northern Kentucky, it will become increasingly important to grow in a manner that allows for the protection of natural resources while maintaining a high quality of life for its residents. The next logical step toward a comprehensive green infrastructure approach in Northern Kentucky is to develop several successful demonstration projects. These projects will help act as a "catalyst" for bolder efforts in the future. Some examples have already been built, as demonstrated at the Sanitation District No. I headquarters. Hundreds of other green infrastructure opportunities, both large and small, exist in Northern Kentucky. The ultimate goal of this handbook is to provide the inspiration for their discovery.



Figure 6-15: Sunset on the Ohio River in Northern Kentucky.